

FY23 Strategic Initiatives Research and Technology Development (SRTD)

Optimization and System Integration of Photonics for Advanced Astrophysics Mission Concepts

Principal Investigator: Jeffrey Jewell (398); Co-Investigators: James Wallace (326), Dylan McKeithen (383), Ryan Briggs (382), Luis Pereira da Costa (389), Tobias Wenger (389), Constantine Sideris (USC), Nemanja Jovanovic (Caltech), Pradip Gatkine (Caltech)





Figure 1E. Dynamic Photonic Integrated Circuit (PIC), with 21 input and output waveguides, capable or sorting an arbitrary mode with all the light in that mode output on one channel. The PIC can be integrated into the back end of the lantern array in figure 1B, providing an end-to-end photonic coronagraph.

National Aeronautics and Space AdministrationJet Propulsion Laboratory California Institute of Technology Pasadena, California www.nasa.gov

Clearance Number: CL#00-0000 Poster Number: RPC# Copyright 2023. All rights reserved. Significance/Benefits to JPL and NASA:

- Photonic coronagraph concept has the potential to achieve *near ideal performance* for exoplanets very close to the host star
- Directly addresses the key science goal of the Astrophysics Decadal Habitable Worlds Observatory mission concept



PI/Task Mgr. Contact Information: Jeffrey.B.Jewell@jpl.nasa.gov